

Other Products

Control Valves and Actuators



2 / 3-Way Modulating Control Valve (Globe Type)

- For individual room control and for example control of baffles/batteries, hot/cold water, fan convectors, and after-heaters/after-coolers.
- Valve Models : ZTV/ZTR, ZTVB/ZTRB,
Kvs : 0.25-20
DN : 15-40
- Actuator Model : RVAZ4
Supply voltage : 24 V AC/DC
Control signal : 3-point or 0...10 V
Force : 400 N



2 / 3-Way Modulating Control Valve (Globe Type)

- Valve Model : BTV / BTR
Kvs : 0.63 – 39
DN : 15 – 50
- Actuator Model : RVA5
Control signal : 3-point or 0...10 V
Force : 500 N
Stroke time : 60 s



2 / 3-Way Modulating Control Valve (Flange Type)

- For hot and cold water, district heating systems, cooling systems and steam.
- Valve Model : GTVS/GTRS
Kvs : 27 – 310
DN : 40 – 150
- Actuator Model : RVA
Control signal : 3-point or 0...10 V
Force : RVA5 (500 N)
RVA10 (1000 N)
RVA18 (1800 N)
RVA25 (2500 N)



Radiators, underfloor chilled beam control valve

- Valve Models :-
RTV (2way)
Kvs : 1.2 – 1.4
DN : 10 – 15
- FVR (2-way)
Kvs : 0.01...1.1 (adjustable)
DN : 10 – 20
- CTV (2-way for after treatment systems)
Kvs : 0.12 – 1.9 (adjustable)
DN : 10 – 20
- Actuator Models :-
RTA – thermal actuators
Supply voltage : 24 V AC/DC or 230 V AC
Control signal : On/off or 0...10 V
Force : 100 N



2 / 3-Way Zone Valves With Thermal Actuator

- For control of cold and hot water in fan-coil or chilled beams applications.
- Valve Models :-
ZTTV/ZTTR/ZTTB
Kvs : 0.25 – 4
DN : 15 – 20
- Actuator Models :-
RTAOM – Thermal actuators
Supply voltage : 24 V AC/DC or 230 V AC
Control signal : On/off
Force : 100 N



2 / 3-Way FCU Motorised Valve With Actuator (Detachable)

- Valve Model :-
DFCM
Kvs : 3.2 – 5.7
DN : 15 – 25
Supply voltage : 230 V AC
Control signal : On/off