

Refrigeration









WING Basic (Special Refrigeration Controller)

- Direct live and neutral load connections for reduction of wiring costs.
- Up to 8 push buttons with direct action for user friendly interface\Hot Key connector for a quick and easy programming.
- Connection for X-REP remote display (L and K formats, for LS format is an alternative to TTL output).
- Serial connection to monitoring systems (L, LS and K formats).
- Display with red LED (10,5mm high) and icons (L, LS and CX formats), 13,2mm high (VS and V formats).
- Ultra reduced depth of LS & VS formats.^{new!}
- TTL serial connection for monitoring systems.

FEATURES

	XW20L	XW20LS	XW20VS	XW20K	XW60L	XW60V	XW60VS	XW60K
Display: n° digits	± 3 d.p.	± 3 d.p.	± 3 d.p.	± 3 d.p.				
Keyboard: push buttons	6	6	6	6	Cx620 - T620 V620:6	6	5	CX620 - T620 -
Power supply	24,110,230Vac	24,110,230Vac	24,110,230Vac	24,110,230Vac	24,110,230Vac	24,110,230Vac	24,110,230Vac	24,110,230Va
Probe inputs								
Thermostat	NTC/PTC	NTC/PTC	NTC/PTC	NTC/PTC	NTC/PTC	NTC/PTC	NTC/PTC	NTC/PTC
Defrost		NTC/PTC			NTC/PTC	NTC/PTC	NTC/PTC	NTC/PTC
Condenser	NTC/PTC			NTC/PTC	NTC/PTC			NTC/PTC
Display	NTC/PTC		NTC/PTC	NTC/PTC	NTC/PTC		NTC/PTC	NTC/PTC
Digital inputs								
Alarm, start defrost, door switch, pressure switch	config	config*	config	config	config	config	config	config
DI 2		config				config		
Relay outputs								
Compressor	20A	20A	16A	20A	20A	8A, 20A opt	16A	20A
Defrost					8A	8A	16A	16A
Fans					8A	8A	8A	8A
Light, ON/OFF	8A, 16A opt	8A	16A	16A	8A, 16A opt	16A		16A
Alarm, AUX								
Other								
Hot Key/Prog Tool Kit output	pres	pres	pres	pres	pres	pres	pres	pres
Serial output	TTL	TTL		TTL	TTL			TTL
Remote display output	X-REP opt	X-REP opt		on keyboard	X-REP opt			
Buzzer	opt	opt	opt		opt	opt	opt	on keyboard
Real time clock	opt	opt			opt			

LINE DIAGRAM



ACCESSORIES



Steel Front

Blue LED



LS

VS



Hot Key

XJ485CX (MODBUS-RTU)