



## iProGENIUS (Programmable Logic Controller - PLC)

### • Hardware Details :

- LINUX Operative System.
- ISaGRAPH® Software.
- 200MHz CPU.
- 32bit Processor.
- 32MB RAM Memory.
- 20VA Power Absorption.

### • Applications :

- Complete Compressor Rack Controls (iProRack) <sup>new</sup>
- Complete Ammonia Refrigeration system controls <sup>new</sup>
- Multiple condenser/ evaporator controls for cold room
- Typical food processings like vanaspatti
- Pharmaceutical cold storage controls with BMS connectivity
- Complete Fruit Ripening Process controls <sup>new</sup>
- Complete Screw Compressor (with steps / stepless) Management <sup>new</sup>




INDIA Approved

## FEATURES

	IPG108D	IPG110D	IPG115D	IPG208D	IPG210D	IPG215D
Power Supply	24Vac/dc-TF20D	24Vac/dc-TF20D	24Vac/dc-TF20D	24Vac/dc-TF20D	24Vac/dc-TF20D	24Vac/dc-TF20D
Display	opt			opt		
Format	4 DIN Rail	10 DIN Rail	10 DIN Rail	4 DIN Rail	10 DIN Rail	10 DIN Rail
<b>Probe Inputs</b>	<b>6 config</b>	<b>10 config</b>	<b>10 config</b>	<b>6 config</b>	<b>10 config</b>	<b>10 config</b>
0÷1V - 0÷5V - 0÷10V - 0÷20mA - 4÷20mA						
<b>Digital Inputs</b>	<b>11 config</b>	<b>20 config</b>	<b>20 config</b>	<b>11 config</b>	<b>20 config</b>	<b>20 config</b>
Opto-insulated						
<b>Relay Outputs</b>	<b>8x5A</b>	<b>9x5A + 1x8A</b>	<b>12x5A + 3x8A</b>	<b>8x5A</b>	<b>10x5A</b>	<b>15x5A</b>
Configurables						
<b>Other Outputs</b>						
PWM for Fan Speed Modules		2 config	2 config			
0÷10V, 4÷20mA for Fan Speed Modules	4 config	2 config	2 config	4 config	2 config	2 config
0÷10V for External Relay Drivers	4 config	4	4	4 config	4	4
Remote Keyboard	1xVGIPG	2xVGIPG	2xVGIPG	1xVGIPG	2xVGIPG	2xVGIPG
Rs485	slave	master / slave	master / slave	slave	master / slave	master / slave
USB	pres	pres	pres	pres	pres	pres
External Modem		GSM, XWEB opt	GSM, XWEB opt		GSM, XWEB opt	GSM, XWEB opt
LAN	pres			pres		
CANBus		pres	pres		pres	pres
Ethernet Enabled		opt	opt		opt	opt
<b>Connections</b>						
Disconnectable + Screw	pres	pres	pres	pres	pres	pres
Bayonet + Screw						
<b>Other</b>						
Internal Modem		opt	opt		opt	opt
RTC	pres	pres	pres	pres	pres	pres
USB-Ethernet Adapter	opt			opt		
Flash Memory	16MB	128MB	128MB	16MB	128MB	128MB

## ACCESSORIES



Connectivity Module For VGI, RS485 (M/S), LAN, CANBus



EEV Module



Transformer and Cable Kit



Development Tools